PRACTICAL VEHICLE TEST FOR VELOMOBILES AND RECUMBENTS

1. KOMFORT (45)

Suspension (10)				
Suspension (10)				
Range of the spring, heavier loaded axle				
	2 - 5 cm	1		
	> 5 - 1 0 cm	2		
	> 10 cm	4		
Range of the spring, othe	r axle			
	2 - 4 cm	1		
	> 4 - 8 cm	3		
Seat suspension				
	Soft seat cover	1		
	Tightened web	2		
	Seat suspension	1		
Seating komfort (10)		-		
Sweat permeability				
e nour pornouoliny	Moulded seat with holes	1		
	With permeable cover	2		
	Perm. tightened web	3		
Seat above bottom brack	a a a a a a a a a a a a a a a a a a a	Ľ		
		4		
	<pre>< -10 to 0 cm (under b.) > 0 to 10 cm</pre>	1 2		
	> 10 cm	2		
A divertals little	> 10 CIII	<u>ہ</u>		
Adjustability				
	Seat adj. lengthwise	2		
	Bottom br. adj. lengthw.	1		
	Back slope	1		
Rain protection (25)				
Rain protection driver		_		
	Front fairing	7		
	Upper part of the body	5		
	Head	4		
	Protection from the side	2		
Splash protection of the wheels				
	Splasher rear wheel	1		
	Splasher front wheel	1		
		_		
	Splash guard mounted	1		
Chain protection				
	Partially	1		
	Full protection	2		
Baggage protection				
	Completely closed	1		
1	Completely closed	1		

2. HANDINESS (15)

Weight (5)	Tandem: Weight /2	
	< 10 kg	5
	> 10 - 12 kg	4
	> 12 - 15 kg	3
	> 15 - 20 kg	2
	> 20 - 25 kg	1

Get on, get off, parking (10)				
	To both sides	2		
Access height				
	< 20 - 30 cm	3		
	> 30 - 40 cm	2		
	> 40 - 50 cm	1		
Total length				
	< 180 cm	3		
	> 180 - 200 cm	2		
	> 200 - 220 cm	1		
Parking stand				
	Stand or > 2 wheels with parking brake	2		

3. SECURITY (40)

Sight (15)				
	Eye level > 100 cm	3		
	Back steeper than 45°	1		
Windscreen				
	None	7		
	With wiper	4		
	Slope steeper than 35°	3		
Looking back		_		
	Rear-view mirror mounted	1		
	Direct view back by turning	3		
Lighting and conspicu	ousness (15)			
	Head light	1		
	With halogen bulb	2		
	Back light	1		
	Head- and back reflector	1		
	Additional reflecting spots > 100 cm ²	1		
	Accu light	1		
	Fairing bright or luminescent colour	3		
	Bell	1		
Turning				
	Sign by hand or turn signals	5		
Security in accidents (1	10)			
	No handlebar in front of body	2		
	No sharp edges	1		
	Seating height < 60 cm	2		
Full fairing with side protection				
	hard mould or tube	5		